



70 - 700 Nm

MAX SPEED 21 RPM

BLUETOOTH CONNECTIVITY

TORQUE + ANGLE LIMITS

DATA LOGGING

TORQUE CHECK FUNCTION

SPECIFICATIONS

- **TORQUE RANGE:** 70 - 700 Nm.
- **SPEED:** 21 RPM.
- **WEIGHT:** 3,5 Kg with battery, excluding reaction arm and impact socket.
- **SQUARE DRIVE:** 3/4 inch square drive.
- **BATTERY:** Two 18V Li-ion batteries 5.2Amp/93 Wh.
- **NOISE LEVEL:** Maximum 65 dB.
- **TORQUE SETTING:** Steps of 1 Nm.
- **REPEATABILITY ON SAME JOINT*:** +/- 2%.

* Test results from RAD's certified calibration lab

SUITABLE REACTION ARMS

Standard



PN: 19260

Deep socket



PN: 13367

Double ended



PN: 13368

Blank



PN: 13364

Double ended blank



PN: 13365

Safety sliding



PN: 25243

DIMENSIONS IN MM



TOOL KIT INCLUDING

- MB-RAD 700
- Standard reaction arm (PN: 19260)
- Retaining ring (PN: 12733)
- Two batteries with quick charger
- Calibration certificate
- Usermanual
- Safety instructions on USB stick
- Weatherproof storage case



ACCESSOIRES

Product	Part number
8.0 Ah LiHD battery (144 wh) (option)	200473
Double Safety Trigger (option)	25949
Nose extension - 305 mm (option)	14195



Non
Impacting



Safe &
Reliable



Lithium-ion
battery



According to
European standards



Accredited
ISO/IEC 17025