



140 - 1.400 Nm

MAX SPEED 10 RPM

BLUETOOTH CONNECTIVITY

TORQUE + ANGLE LIMITS

DATA LOGGING

TORQUE CHECK FUNCTION

SPECIFICATIONS

- **TORQUE RANGE:** 140 - 1.400 Nm.
- **SPEED:** 10 RPM.
- **WEIGHT:** 3,7 Kg with battery, excluding reaction arm and impact socket.
- **SQUARE DRIVE:** ¾ inch square drive.
- **BATTERY:** Two 18V Li-ion batteries 5.2Amp/93 Wh.
- **NOISE LEVEL:** Maximum 65 dB.
- **TORQUE SETTING:** Steps of 1 Nm.
- **REPEATABILITY ON SAME JOINT*:** +/- 2%.

*Test results from RAD's certified calibration lab

SUITABLE REACTION ARMS

Standard	Deep socket	Double ended
PN: 19260	PN: 13367	PN: 13368
Blank	Double ended blank	Safety sliding
PN: 13364	PN: 13365	PN: 25243

DIMENSIONS IN MM



TOOL KIT INCLUDING

- MB-RAD 1400
- Standard reaction arm (PN: 19260)
- Retaining ring (PN: 12733)
- Two batteries with quick charger
- Calibration certificate
- Usermanual
- Safety instructions on USB stick
- Weatherproof storage case



ACCESSOIRES

Product	Part number
8,0 Ah LiHD battery (144 wh) (option)	200473
Double Safety Trigger (option)	25949
Nose extension - 305 mm (option)	14195

