



Torque setting adjustable per 10 Nm

400 - 4.000 Nm

MAX SPEED 3 RPM

DIGITAL TORQUE SETTING

EXTREMELY LIGHT WEIGHT

PLUG AND PLAY

SPECIFICATIONS

- **TORQUE RANGE:** 400 - 4.000 Nm.
- **SPEED:** 3 RPM.
- **WEIGHT:** 6,15 Kg, excluding reaction arm and socket.
- **SQUARE DRIVE:** 1 inch square drive (replaceable).
- **NOISE LEVEL:** Maximum 87 dB.
- **TORQUE SETTING:** 10 Nm incremental via torque chart in table mode.
- **ACCURACY:** 5% on full scale.

SUITABLE REACTION ARMS

Standard



PN: 27022

Deep socket



PN: 24814

Double ended



PN: 25437

Blank



PN: 24813

Double ended blank




PN: 25016

Safety sliding



PN: 25987

DIMENSIONS IN MM



TOOL KIT INCLUDING

- V-RAD SELECT 4000
- Standard reaction arm (PN: 27022)
- Retaining ring (PN: 21474)
- Calibration certificate
- Usermanual
- Safety instructions on USB stick
- Weatherproof storage case
- Standard EU Socket



ACCESSOIRES

Product	Part number
Tool hanger	26800

