



Torque setting adjustable per 10 Nm



- 400 - 2.000 Nm**
- MAX SPEED 19 RPM**
- AUTOMATIC 2-SPEED**
- AUTO REACTION ARM BACK OFF**
- BRUSHLESS MOTOR**
- DOUBLE SAFETY TRIGGER**  
*OPTION*

## SPECIFICATIONS

- **TORQUE RANGE:** 400 - 2.000 Nm.
  - **SPEED:** Automatic gearbox with 19 RPM.
  - **WEIGHT:** 5,4 Kg with battery, excluding reaction arm and impact socket.
  - **SQUARE DRIVE:** 1 inch square drive.
  - **BATTERY:** Two 18V Li-ion batteries 5.2 Amp/93 Wh.
  - **NOISE LEVEL:** Maximum 65 dB.
  - **TORQUE SETTING:** Steps of 10 Nm or ft. lbs
  - **REPEATABILITY ON SAME JOINT\*:** +/- 3%.
- \* Test results from RAD's certified calibration lab

## SUITABLE REACTION ARMS

| Standard  | Deep socket        | Double ended   |
|-----------|--------------------|----------------|
|           |                    |                |
| PN: 14213 | PN: 18480          | PN: 19094      |
| Blank     | Double ended blank | Safety sliding |
|           |                    |                |
| PN: 17888 | PN: 19093          | PN: 25242      |

## DIMENSIONS IN MM



## TOOL KIT INCLUDING

- B-RAD Offset 2000-2
- Standard reaction arm (PN: 14213)
- Retaining ring (PN: 17367)
- Two batteries with quick charger
- Calibration certificate
- Usermanual
- Safety instructions on USB stick
- Weatherproof storage case



## ACCESSOIRES

| Product                               | Part number |
|---------------------------------------|-------------|
| 8,0 Ah LiHD battery (144 wh) (option) | 200473      |
| Double Safety Trigger (option)        | 25949       |

